

CS-FMRC-05 - Ford 4.5" Progressive Lift Coils
CS-FLRC-05 - Ford 2.5" Linear Leveling Lift Coils

NOTE:

Please review the product instructions prior to attempting installation to ensure installer is equipped with all tools and capabilities necessary to complete the product installation. We recommend thoroughly reading the instructions at least twice prior to attempting Installation.

Before beginning disassembly of the vehicle, check the "What's Included" section of the instructions to ensure you've received all parts necessary to complete installation. Further, verify that the parts received are PROPER TO YOUR application (year range, motor, etc.) to avoid potential down-time in correcting potential discrepancies. Any discrepancies will be handled by Carli Suspension and the correcting products will be shipped UPS Ground.

LIFETIME PRODUCT WARRANTY

Carli Suspension provides a limited lifetime product warranty against defects in workmanship and materials from date of purchase to the original purchaser for all products produced by Carli Suspension. Parts not manufactured by, but made to Carli Suspension's specifications by third party manufacturers will carry a warranty through their respective manufacturer. (i.e. King Shocks, Bilstein Shocks, Fox Shocks). Deaver Leaf Spring's warranty will be processed by Carli Suspension.

Proof of purchase (from the original purchaser only) will be required to process any warranty claims. Carli Suspension products must be purchased for the listed Retail Price reflected by the price listed on the Carli Suspension Website at the time of purchase. Carli Suspension reserves the right to refuse warranty claims made by any customer refusing or unable to present proof of purchase, or presenting proof of purchase reflecting a price lower than Carli Suspension's Retail Price at the time the item was purchased.

Carli Suspension's Limited Lifetime Warranty excludes the following parts which are subject to wear: Track Bar Bushings, Track Bar Heim Joints, Limit Straps, Control Arm Bushings, Radius Arm Bushings, Shock Bushings, Sway Bar End Link Heim Joints, Shock Seals, Shock Bearings, and Corrosion on Shock Shafts or Bodies. These items will be warranted for a period of 60 days from the date of purchase only if determined to be installed properly signifying manufacturing defect. Carli Suspension cannot warrant a product's cosmetic finish due to the varying extreme elements that may be encountered.

Any alterations, modifications, or improper installation, of the product will void this warranty. Products should be inspected for defect upon receipt and approved before installation. Any defect in NEW product will be warranted if returned before installation in its original packaging. Carli Suspension's obligation under this warranty is limited to the repair or replacement of the defective product only. All costs of removal, installation or reinstallation, freight charges, incidental or consequential damage are expressly excluded from this warranty.

Carli Suspension is not responsible for damages and/or warranty of other vehicle parts related or non-related to the installed Carli Suspension product. This warranty shall not apply to any product that has been subjected to accident, negligence, alteration, abuse or misuse as determined by Carli Suspension. Carli Suspension reserves the right to refuse warranty claims if produced parts are combined and/or substituted with other aftermarket suspension products. Combination and/or substitution of other aftermarket suspension components may cause premature wear and/or product failure. Carli Suspension reserves the right to change/alter product without obligation to update any previously purchased products.



What's Included

- 4.5" Lift: (2) Multi-Rate Carli Coil Springs (side specific)
OR
- 2.5" Lift: (2) Linear Rate Coil Springs (not side Specific)

System Notes:

Springs should be installed after Brake Lines and Radius Arm drop Brackets (4.5" Lift ONLY). If installing a Dominator 3.0", the Fabricated Coil Buckets should be installed first.

Installation Instructions

NOTE: This instruction is intended to be a continuation of a modular, full kit installation; if you're just installing the coil springs, there may be additional steps involved not mentioned in this document.

1. Fully extend front suspension and remove factory coils.
2. Place the factory isolator on top of the Carli coils and install.
NOTE: 4.5" coils are side specific! Next to the logo on each coil will be a (D) for driver side or (P) for passenger side.
2.5" lift coils are not side specific.
NOTE: Backcountry or Pintop ONLY: Place supplied Carli front reservoir mount on top of coil spring isolator during coil spring installation.
3. Install the new Carli coils ensuring they are indexed properly in the lower mounts. Spin them while watching the bottom spring end drop into the proper location.
4. Jack up under the axle once the coils are properly seated in the upper and lower mounts. This will hold their position during shock installation.
5. Proceed to the next step in the installation instructions.