

**NISSAN REPLACEMENT CAM  
BOLTS**

---

*This part should only be installed by personnel who have the necessary skill, training and tools to do the job correctly and safely. Incorrect installation can result in personal injury, vehicle damage and / or loss of vehicle control.*

---

**Plan Ahead - Read All Instructions BEFORE installing part.**

1. Before beginning alignment, check for loose or worn parts, tire pressure and odd tire wear.
2. Raise vehicle by frame.
3. Replace cam bolts one at a time. Remove one upper "A" arm mounting bolt.
4. Install cam bolt by placing a cam at head of the bolt. Fit bolt with cam in upper control arm. Mount next cam then place nut on bolt and tighten lightly.
5. Install other control arm bolt in same manner.
6. Re-install tire and wheel assembly and re-compensate alignment equipment.
7. Adjust cams to desired caster/camber settings then torque nuts to manufacturer specification while holding bolt head.
8. Adjust toe and road test vehicle.

**Caution: Always use appropriate safety devices to support the weight of the vehicle while servicing suspension components. Always check for proper clearance between suspension components and other components of the vehicle.**



**Specialty  
Products  
Company**<sup>®</sup>

P.O. Box 923 • Longmont, CO 80502 • (303) 772-2103

www.specprod.com • www.spcperformance.com

Email: info@specprod.com

Printed in U.S.A.

**Toll Free Technical Hot Line: 1-800-525-6505**