

NISSAN CAMBER/CASTER KIT

This part should only be installed by personnel who have the necessary skill, training and tools to do the job correctly and safely. Incorrect installation can result in personal injury, vehicle damage and / or loss of vehicle control.

1. Before beginning any alignment, check for loose or worn parts, tire pressure, and odd tire wear.
2. Take alignment readings and determine the amount of camber/caster change needed.
3. Raise vehicle by frame and remove the lower "A" arm mounting bolts.

Caution: Always use appropriate safety devices to support the weight of the vehicle while servicing any suspension component.

4. Install cam bolts by placing one cam on the head of each bolt.
5. Install the bolts through the "A" arm, install the cam washers, install the nuts and tighten slightly.
6. Adjust cam bolts to desired camber/caster settings and torque nuts to manufacturer's specifications while holding the head of the bolt.

Always check for proper clearance between suspension components and other components of the vehicle.

7. Adjust toe and road test vehicle.



**Specialty
Products
Company**[®]

P.O. Box 923 • Longmont, CO 80502 • (303) 772-2103

www.specprod.com • www.spcperformance.com

Email: info@specprod.com

Printed in U.S.A.

Toll Free Technical Hot Line: 1-800-525-6505

©2011 Niwot Corp. dba Specialty Products Co. • Form No.87520INS • Rev.3/11