

NEW!

450P-RV ENHANCED FLOW AUTOMATIC PORTABLE COMPRESSOR

150 PSI / 2.19 CFM

Max Amp Draw: 23-Amp

P/N 45157

VIAIR Portables compressors with Enhanced Flow Technology (EF) provide faster inflation without compromising the legendary durability that VIAIR is known for. All kits come complete with everything you will need to manage your tire inflation needs. Be smart and travel with a VIAIR Portable compressor on all your on and off-road trips.



Performance Data					
PSI	CFM	A	BAR	LPM	A
0	2.19	11	0	62.0	11
40	1.70	18	3	48.0	18
90	1.34	21	6	39.0	21
150	0.95	22	10	28.0	22

*Tolerances (±) define a range within which actual performance may fall.

RV Tire Fill Rates	
245/70R19.5	Fill Rate
60 to 80 PSI	2 min. 02 sec. (± 10 sec.)
80 to 90 PSI	1 min. 02 sec. (± 05 sec.)
90 to 110 PSI	2 min. 35 sec. (± 10 sec.)
255/70R22.5	Fill Rate
80 to 90 PSI	1 min. 41 sec. (± 05 sec.)
90 to 110 PSI	3 min. 47 sec. (± 10 sec.)
110 to 120 PSI	1 min. 59 sec. (± 05 sec.)
275/80R22.5	Fill Rate
80 to 90 PSI	2 min. 15 sec. (± 10 sec.)
90 to 110 PSI	2 min. 27 sec. (± 10 sec.)
110 to 120 PSI	2 min. 40 sec. (± 10 sec.)

Please contact your sales representative for pricing.

FEATURES:

- EF (Enhanced Flow) Technology
- 2-Pin SAE Power connection with 40-Amp inline fuse holder
- Gas Station-Style Tire Inflation Gun with 160 PSI Gauge
- Primary & Extension Air Hoses
- 45-Degree Extended Reach Chuck
- 90-Degree Twist on Chuck
- 3 pc. Inflation Tips kit and Presta valve adapter
- Patented I-Beam Sand Tray
- Stealth Black Look
- Rugged Carry Bag
- High Flow output for Oversize Tires

SPECIFICATIONS:

- 12-Volt
- Permanent Magnetic Motor
- Duty Cycle: 100% @ 100 PSI
- Max. Working Pressure: 150 PSI
- Max. Amp Draw: 23-Amps
- Ingress Protection Rating: IP54
- Max. Ambient Temp: +158°F
- Min. Ambient Temp: - 40°F
- Dimensions: 12.4" x 5.8" x 7.4"
- Net Weight: 13.00 lbs.
- Power Cord Length: 6 ft.
- Primary Air Hose Length: 30ft.
- Extension Air Hose Length: 30ft.

