

ROUGH COUNTRY

SUSPENSION SYSTEMS®



WARNING: This product contains a chemical known to the State of California to cause Cancer and Reproductive Harm. For more information, go to www.P65Warnings.ca.gov.

2022-2024 TOYOTA TUNDRA REAR WHEEL WELL LINER

PLEASE READ INSTRUCTIONS CAREFULLY BEFORE STARTING THE INSTALLATION.

NOTE: FOR EASIER INSTALLATION, REMOVE THE TIRE.

INCLUDED IN HARDWARE KIT:

1.



Driver Side Liner
1 pc

2.



Passenger Side Liner
1 pc

3.



Plastic Retainer
4 pcs

4.



10mm Bolt
4 pcs

TOOLS NEEDED:

Socket Wrench with 10mm Socket
Pry Tool or Flathead Screwdriver

PREPARATIONS:

- Please clean the interior panels of the rear wheel well.

REAR WHEEL WELL LINER INSTALLATION



Use a pry tool or flathead screwdriver to remove 2 plastic retainers at top rear of wheel well.



Slide the Rear Wheel Well Liner behind wheel at rear of vehicle. It is helpful to tilt the liner at a 45-degree angle at front of wheel and then straighten it out once it's behind the wheel.



Install 2 supplied Plastic Retainers through top holes in Wheel Well Liner and into holes vacated in Step 1.



Use a 10mm socket to install a supplied 10mm Bolt through hole at front of Wheel Well Liner and into factory grommet in existing wheel well liner.



Use a 10mm socket to install a supplied 10mm Bolt through hole at rear of Wheel Well Liner and into factory grommet in existing wheel well liner.



Tighten all screws. Installation is complete; repeat for other side.